

PRODUCT DESCRIPTION

Xtreme ATF VI is formulated with synthetic base oils and an additive package suitably balanced in order to give the product the properties required by the Dexron VI.

This product guarantees:

- Exceptional low temperature performance,
- improved thermal and oxidation stability,
- excellent frictional properties that provide smooth gear shifting at low temperatures and help to prevent transmission vibration,
- exceptional resistance to the formation of sludge and deposits,
- Prolonged life of the fluid.

APPLICATIONS

The product Xtreme ATF VI is recommended as hydraulic fluid for modern automatic transmissions. The high technology used enables longer transmission life.

Xtreme ATF VI is recommended for Dexron VI and Mercon LV automatic transmissions. It can also be used in cars with 6-speed automatic transmission from Audi, BMW, Mini Cooper, Jaguar, Peugeot, Saab, Volvo, VW and Porsche

PERFORMANCE LEVELS AND APPROVALS

GM DEXRON VI
 FORD MERCON LV
 JASO 1A-LV
 ALLISON TES 228 C-3/C-4
 MB 236.12/236.14/236.41
 HONDA /ACCURA DW-1
 HYUNDAI/KIA SP IV-SPH-IV/NWS-9638-T5/040000C90SG
 JAGUAR FLUID 8432
 LAND ROVER TYK 500050/LR0022460
 MASERATI 231603
 MAZDA FZ/FW 6A EL/6AX EL
 MITSUBISHI DIAQUEEN SP IV/DDIAQUEEN J3
 NISSAN /INFINITY MATIC S
 PORSCHE # 000 043 304 000
 SAAB 93 165 147-AW-1
 TOYOTA LEXUS ATF WS
 VW/AUDI G 052 533/G 055-005-A/G 055-005-A2/ G 055 540 (A2)
 ZF-LIFEGUARD 6

TYPICAL CHARACTERISTICS

ATF VI	Testing procedure	Typical Values
Color	Visual	Red
Density @ 15°C, kg/m ³	ASTM D 1298	≥840,0
Cinematic Viscosity @40°C, cSt	ASTM D 445	≤32
Cinematic Viscosity @100°C, cSt	ASTM D 445	≤6
Viscosity Index	ASTM D 2270	≥160
Pour Point,°C	ASTM D 97	≤-42
Flash Point,°C	ASTM D 92	≥180

MsdS of all our products are available under request

The information contained in this statement are considered correct at the time of writing the same, but changes in formulation or changes in the performance profile of the product occurred in the days following that date may affect its accuracy. In any case, the above information is indicative and do not constitute specification.