

PRODUCT DESCRIPTION

Xtreme 1001 15W-40 is a premium quality multi-grade lubricant based on highly refined mineral oils and selected additives. It gives outstanding performances in naturally aspirated or turbocharged engines, fuelled by gasoline or diesel, for passenger cars and in light vans.

It shows the following main benefits:

- high oxidation resistance which reduces deposit formation,
- enhanced engine protection against wear,
- good detergency/dispersion properties giving cleaner engines.

APPLICATIONS

Xtreme 1001 15W-40 is suitable for engines with catalytic converters and performs very well in engines operating under vehicle manufacturers' recommended maintenance procedures. It is suitable for extended drain intervals where specified by the engine manufacturer.

PERFORMANCE LEVELS AND APPROVALS

API SL/CF
ACEA A3/B3
MB 229.1
VW 501.01/ 505.00

TYPICAL CHARACTERISTICS

Xtreme 1001 15W-40	TESTING PROCEDURE	TYPICAL VALUES
SAE Viscosity Grade		15W-40
Density @15°C, Kg/m ³	ASTM D 1298	870
Kinematic viscosity @100°C, cSt	ASTM D 445	14,5
Viscosity Index	ASTM D 2270	≥ 130
Pour Point, °C	ASTM D 97	≤-21
Flash Point, °C	ASTM D 92	220