

PRODUCT DESCRIPTION

Xtreme 8009 C4 ECO SYNT 5W-30 is a fully synthetic lubricant formulated with base oils and a package of additive "LOW SAPS", specifically designed to extend the life and maintain the efficiency of Exhaust Car Emission Reduction Systems for modern gasoline and diesel engines.

Xtreme 8009 C4 ECO SYNT 5W-30 provides the following advantages:

- excellent anti-wear protection over a wide temperature range,
- excellent thermal stability and oxidation resistance.
- better protection against the formation of sludge,
- excellent performance at high and low temperatures.

APPLICATIONS

Xtreme 8009 C4 ECO SYNT 5W-30 is recommended in all new generations cars with gasoline and diesel engines with exhaust emission control systems where the manufacturer requires the use of an ACEA C4 lubricant.

PERFORMANCE LEVELS AND APPROVALS

ACEA C4
MB 226.51/229.31
RENAULT RN 0720

TYPICAL CHARACTERISTICS

Xtreme 8009 C4 ECO SYNT 5W-30	TESTING PROCEDURE	TYPICAL VALUES
SAE Viscosity Grade	-	5W-30
Density at 15°C, Kg/m ³	ASTM D 1298	≥ 850,0
Viscosity at 100°C, cSt	ASTM D 445	9,3 ÷ 12,5
Viscosity Index	ASTM D 2270	≥ 160
Pour Point, °C	ASTM D 97	≤ -36
Flash Point, °C	ASTM D 92	≥ 218
TBN, mg KOH/g	ASTM D 2896	≥ 6
Sulfated ash, %p	ASTM D 874	≤ 0,5