

## PRODUCT DESCRIPTION

Xtreme MOTO 4T 15W40 is a lubricant formulated with carefully selected mineral base oils and additives for 4-stroke engines and motorcycle clutch units of any brand and capacity, air or water cooled.

Xtreme MOTO 4T 15W40 guarantees the following features:

- Excellent anti-wear capacity,
- Extraordinary oxidation resistance and thermal stability,
- High detergency / dispersion capacity with resistance to the formation of deposits.

Xtreme MOTO 4T 15W40 has a carefully balanced additive package that offers the following advantages:

- Ensuring maximum protection against friction,
- drastically reducing the wear of mechanical parts,
- facilitating the insertion of the driving gears, reducing oil consumption.
- Excellent low and high temperature performance under continuous driving conditions.

## APPLICATIONS

Xtreme MOTO 4T 15W40 provides maximum protection for medium and high cylinder capacity engines with one, two, three or four cylinders, and ensures the care of all its components even under severe conditions of use and high speeds.

## PERFORMANCE LEVELS AND APPROVALS

API SL  
JASO MA

## TYPICAL CHARACTERISTICS

Xtreme Moto 4T 15W40	TESTING PROCEDURE	TYPICAL VALUES
SAE grade		15W-40
Density, kg/m <sup>3</sup>	ASTM D 1298	≥ 855
Kinematic viscosity, cSt a 100°C	ASTM D 445	12,5 ÷16,3
Viscosity index	ASTM D 2270	≥145
Pour point, °C	ASTM D 97	≤-27
Flash point, °C	ASTM D 92	≥ 210