

PRODUCT DESCRIPTION

Xtreme 8006 SP ECO SYNT 5W-30 is a fully synthetic engine oil formulated with selected base oils and high-tech additives to guarantee high protection of direct injection turbocharged gasoline engines and the emissions after-treatment system.

Xtreme 8006 SP ECO SYNT 5W-30 provides the following advantages:

- Optimal protection against pre-ignition events (LSPI) occurring at low speed and high torque,
- high resistance to oxidation which reduces the formation of deposits,
- good detergent/dispersant properties that allow you to clean engines and protect from mud,
- outstanding engine protection against wear, corrosion and rust which guarantees long engine life,
- excellent performance at high and low temperatures.

APPLICATIONS

Xtreme 8006 SP ECO SYNT 5W-30 is recommended for passenger vehicles, SUVs and light vehicles as well as for American, Japanese and Korean automotive manufacturers where a 5W-30 lubricant that meets API SP and ILSAC GF-6 or earlier specifications is required.

PERFORMANCE LEVELS AND APPROVALS

ACEA C2/C3
API SP
ILSAC GF-6A
MB 229.51/229.52
BMW LL-04
GM Dexos 2

TYPICAL CHARACTERISTICS

Xtreme 8006 SP ECO SYNT 5W-30	TESTING PROCEDURE	TYPICAL VALUES
SAE Viscosity Grade		5W-30
Density @ 15°C, Kg/m ³	ASTM D 1298	≥ 850
Viscosity @ 100°C, cSt	ASTM D 445	9,3 ÷ 12,5
Viscosity Index	ASTM D 2270	≥ 165
Pour Point, °C	ASTM D 97	≤ -33
Flash Point, °C	ASTM D 92	≥220