

PRODUCT DESCRIPTION | Xtreme INBOARD 4T 15W-40 is a high-performance multigrade lubricant designed for use in 4-stroke diesel and gasoline inboard engines.

Xtreme INBOARD 4T 15W-40 features the following characteristics:

- Excellent low-temperature fluidity to enable quick lubrication during cold starts,
- High oxidation resistance and excellent engine cleanliness,
- Good detergency and dispersancy to reduce sludge formation, avoiding the risk of filter blockages,
- Excellent protection against mechanical wear and salt corrosion even during prolonged periods of inactivity.

APPLICATIONS | Xtreme INBOARD 4T 15W-40 is ideal for all types of diesel and gasoline engines in the marine sector. It can be mixed with all types of commercially available engine oils. It is recommended to adhere to the specifications and standards of engine and vehicle manufacturers.

PERFORMANCE LEVELS AND APPROVALS | API CI-4/SL
ACEA E7
MB 228.3
VOLVO VDS-3
MAN M3275
MTU TYPE 2
MACK EO-N / EO-M Plus
RENAULT TRUCKS RLD/RLD-2
CUMMINS CES 20076/77/78
CATERPILLAR ECF-2/ ECF-1-a
DEUTZ DQC III-18
DETROIT DIESEL DDC 93K215

TYPICAL CHARACTERISTICS

Xtreme INBOARD 4T 15W-40	TESTING PROCEDURES	TYPICAL VALUES
SAE grade	-	15W-40
Density @15°C, kg/m ³	ASTM D 1298	≥860
Kinematic Viscosity @100°C, cSt	ASTM D 445	12,5 ÷ 16,3
Viscosity Index	ASTM D 2270	≥ 140
Pour Point,°C	ASTM D 97	≤-30
Flash Point,°C	ASTM D 92	≥220

Le schede di sicurezza di tutti i prodotti sono disponibili su richiesta.