

## PRODUCT DESCRIPTION

Xtreme TRUCK SYNT 10W-40 is a UHPDO premium quality multi-grade lubricant blended with a synthetic base oil obtained by hydro-isomerisation which constructs branched paraffins from waxes. The high quality of the base oil and the selected additives assure outstanding service performance to the product.

This product has the following main properties:

- Relevant low temperature property to enable rapid lubrication at cold starting,
- High oxidation resistance and excellent engine cleanliness,
- Exceptional protection versus ring sticking,
- Good detergency/dispersancy properties for the best soot control,
- Excellent wear control and very limited bore polishing to maximize engine life.

## APPLICATIONS

Xtreme TRUCK SYNT 10W-40 is ideal for a fleet where high ACEA specification products are required. It allows the use of only one product for both E4 and E7 specifications.

The use of this product can provide the following benefits:

- Improved engine cleanliness and wear protection,
- Better protection against sticking bands,
- Excellent low temperature fluidity,
- High possibility of extending the oil changes,
- Outstanding energy saving.

## PERFORMANCE LEVELS AND APPROVALS

UHPDO  
ACEA E4/E7  
ACEA A3/B4  
API CG-4/CH-4/CI-4/ SL  
MB 228.5/228.3  
VOLVO VDS-2 / VDS-3  
MAN M 3275-M 3277 CRT  
RENAULT RXD LEVEL  
MTU TYPE 3  
DEUTZ DQC III – 18  
SCANIA LDF-2

## TYPICAL CHARACTERISTICS

Xtreme TRUCK SYNT 10W-40	Testing procedure	Typical values
SAE Viscosity Grade		10W-40
Density at 15°C, Kg/m <sup>3</sup>	ASTM D 1298	≥855,0
Viscosity at 100°C, cSt	ASTM D 445	12,5 ÷ 16,3
Viscosity Index	ASTM D 2270	≥155
Pour Point, °C	ASTM D 97	≤-30
Flash Point, °C	ASTM D 92	≥220