

PRODUCT DESCRIPTION

Xtreme 1003 20W-50 is a premium quality multi-grade lubricant based on highly refined mineral oils and selected additives. It gives outstanding performances in naturally aspirated or turbocharged engines, fuelled by gasoline or diesel, for passenger cars and in light vans.

It shows following main benefits:

- high oxidation resistance,
- enhanced engine protection against wear,
- outstanding detergency/dispersion properties.

APPLICATIONS

Xtreme 1003 20W-50 meets the below reported specifications.

This product is suitable for engines with catalytic converters. It gives very good performances in engines operating under vehicle manufacturers' recommended maintenance procedures. It is suitable for extended drain intervals where specified by the engine manufacturer.

PERFORMANCE LEVELS AND APPROVALS

API SJ/CF/CF-4
ACEA A3/B4
MB 228.1
VW 501.01/505.00
VOLVO VDS

TYPICAL CHARACTERISTICS

Xtreme 1003 20W-50	TESTING PROCEDURE	TYPICAL VALUES
SAE Viscosity Grade		20W-50
Density at 15°C, Kg/m ³	ASTM D 1298	≥ 870,0
Viscosity at 100°C, cSt	ASTM D 445	16,3 ÷ 21,9
Viscosity Index	ASTM D 2270	≥ 145
Pour Point, °C	ASTM D 97	≤ -21
Flash Point, °C	ASTM D 92	≥ 220