

PRODUCT DESCRIPTION

Xtreme 1004 20W-50 is a premium quality multi-grade lubricant based on highly refined mineral oils and selected additives. It gives outstanding performances in naturally aspirated or turbocharged engines, fuelled by gasoline or diesel.

It shows following main benefits:

- high oxidation and thermal resistance,
- enhanced engine protection against wear,
- outstanding detergency/dispersion properties.

APPLICATIONS

Xtreme 1004 20W-50 is suitable for engines with catalytic converters. It is recommended for gasoline and diesel engines that require API SL quality level of oil and greater protection at high temperatures. It is suitable for extended drain intervals where specified by the engine manufacturer.

PERFORMANCE LEVELS AND APPROVALS

API SL/CF/CF-4
ACEA A3/B4; E2
MB 227.0/228.1
VOLVO VDS-VDS 2
MTU TYPE 2

TYPICAL CHARACTERISTICS

Xtreme 1004 20W-50	TESTING PROCEDURE	TYPICAL VALUES
SAE Viscosity Grade	-	20W-50
Density @ 15°C, Kg/m ³	ASTM D 1298	≥ 870,0
Viscosity @ 100°C, cSt	ASTM D 445	16,3 ÷ 21,9
Viscosity Index	ASTM D 2270	≥ 145
Pour Point, °C	ASTM D 97	≤ -21
Flash Point, °C	ASTM D 92	≥ 220