

PRODUCT DESCRIPTION

Xtreme 3003 10W40 is a synthetic multi-grade lubricant formulated with high quality base oil and additives that guarantee the product to prove excellent in-service performances on engines fueled by gasoline or diesel, naturally aspirated or turbocharged, in passenger cars and light vans.

This product gives the following main benefits:

- suitable low temperature property to enable rapid lubrication after cold starting,
- high oxidation resistance and wear protection to maximize engine life,
- good detergency/dispersion properties for the best control of soot.

APPLICATIONS

Xtreme 3003 10W40 is suggested for use in typical service of gasoline and diesel engines operating under vehicle manufacturers' recommended maintenance procedures.

PERFORMANCE LEVELS AND APPROVALS

ACEA A3/B4
API SJ/CF
MB 229.1
VW 501.01/505.00

TYPICAL CHARACTERISTICS

Xtreme 3003 10W40	TESTING PROCEDURE	TYPICAL VALUES
SAE grade	-	10W-40
Density @15°C, kg/m ³	ASTM D 1298	≥ 850
Kinematic viscosity @100°C, cSt	ASTM D 445	12,5÷16,3
Viscosity index	ASTM D 2270	≥145
Pour point, °C	ASTM D 97	≤-30
Flash point, °C	ASTM D 92	≥220