

PRODUCT DESCRIPTION

Xtreme 4001 5W-50 is a premium quality lubricant blended with synthetic base oils fortified with a balanced component system that provide outstanding performance in many driving situations.

Xtreme 4001 5W-50 shows the following main benefits:

- Excellent low temperature fluidity that gives fast oil flow on start up,
- High oxidation resistance which reduces deposit formation and improve oil life,
- Good detergency/dispersion properties giving cleaner engines,
- Enhanced engine protection against wear,
- Maximizes power output by reducing internal friction by the presence of friction modifier.

APPLICATIONS

Xtreme 4001 5W-50 is suitable for many types of vehicles and operating conditions, from mild to severe. It is intended for use in service typical of gasoline and indirect-injected diesel engines, naturally aspirated or turbocharged, for passenger cars and light vans.

PERFORMANCE LEVELS AND APPROVALS

API SM/CF
ACEA A3/B4
MB 229.1/229.3
BMW LL 01
VW 505.00
PORSCHE

TYPICAL CHARACTERISTICS

Xtreme 4001 5W - 50	TESTING PROCEDURE	TYPICAL VALUES
SAE Viscosity Grade		5W-50
Density @15°C, Kg/m ³	ASTM D 1298	≥850
Kinematic viscosity @100°C, cSt	ASTM D 445	16.3÷21,9
Viscosity Index	ASTM D 2270	≥ 155
Pour Point, °C	ASTM D 97	≤-33
Flash Point, °C	ASTM D 92	≥210