

**PRODUCT DESCRIPTION**

Xtreme 5001 5W40 is a synthetic multi-grade lubricant formulated with high quality base oil and selected additives, among which the friction modifier. The synthetic base oil gives excellent high temperature performance and protection.

Xtreme 5001 5W40 gives the following main benefits:

- Excellent low temperature fluidity that gives fast oil flow on startup,
- High oxidation resistance which reduces deposit formation,
- Good detergency/dispersion properties for the best control of soot giving cleaner engines,
- Enhanced engine protection against wear.

**APPLICATIONS**

Xtreme 5001 5W40 is intended for use in service typical of gasoline and of indirect-injected diesel engines, naturally aspirated or turbocharged, for passenger cars and light vans. It gives an excellent performance in engines operating under vehicle manufacturer's recommended maintenance procedures. It is suitable for extended drain intervals where specified by the engine manufacturer.

**PERFORMANCE LEVELS AND APPROVALS**

API SM/CF  
ACEA A3/B4  
MB 229.3  
BMW LL 01  
VW 500.00/502.00/505.00/505.01  
OPEL B-025  
PORSCHE

**TYPICAL CHARACTERISTICS**

<b>Xtreme 5001 5W40</b>	<b>TESTING PROCEDURE</b>	<b>TYPICAL VALUES</b>
SAE grade	-	5W-40
Density @15°C, kg/m <sup>3</sup>	ASTM D 1298	≥850
Kinematic viscosity @100°C,cSt	ASTM D 445	12,5÷16,3
Viscosity index	ASTM D 2270	≥155
Pour point, °C	ASTM D 97	≤-33
Flash point, °C	ASTM D 92	≥210