

**PRODUCT DESCRIPTION**

Xtreme 7001 5W-30 is an advanced performance full synthetic engine oil made with a careful selection of components and designed to guarantee exceptional cleaning, wear protection and superior performance. It has been expertly designed of the catalyst (Car Emission Reduction Systems) in both diesel and gasoline engines and exceeds the standards required by the main industries and manufacturers of new diesel and gasoline engines generation.

Xtreme 7001 5W-30 guarantees lower consumption together with high performance and engine protection. Thanks to the use of special modifiers of the friction coefficient, it allows the engine to have the maximum power output and enhances the speed of response.

Furthermore, this product has the following characteristics:

- Excellent anti-wear and detergency / dispersion capacity,
- Excellent fluidity at low temperature,
- Exceptional resistance to oxidation,
- Excellent thermal stability.

**APPLICATIONS**

Xtreme 7001 5W-30 is recommended for all newly developed engine types, especially for high-performance petrol engines and latest generation diesel engines, SUVs and light vans. It is particularly suitable for extreme conditions, where conventional oils cannot be used.

The use of this product the following benefits can be obtained:

- Increased engine cleanliness,
- Better engine protection and durability,
- Maximum power supply and engine response speed,
- High reduction of fuel consumption,
- High reduction of harmful emissions.

**PERFORMANCE LEVELS AND APPROVALS**

API SM/CF  
ACEA A3/B4  
MB 229.5  
BMW LL 01  
PORSCHE  
VW 504.00/507.00

**TYPICAL CHARACTERISTICS**

Xtreme 7001 5W30	TESTING PROCEDURE	TYPICAL VALUES
SAE Viscosity Grade		5W-30
Density @15°C, Kg / m <sup>3</sup>	ASTM D 1298	≥ 850,0
Kinematic viscosity @100°C, cSt	ASTM D 445	9,3 ÷ 12,5
Viscosity Index	ASTM D 2270	≥155
Pour Point, °C	ASTM D 97	≤ -33
Flash Point , °C	ASTM D 92	≥ 220