

**PRODUCT
DESCRIPTION**

Xtreme 7005 5W-30 is a synthetic motor oil blended with a high quality base oil and selective additives that ensuring the lubricant presents a very good service performances on engines fueled by gasoline or diesel, naturally aspirated or turbocharged, in passenger cars and light vans.

Xtreme 7005 5W-30 has the following characteristics:

- Excellent low temperature fluidity resulting in rapid flow of oil at the start,
- Outstanding anti - wear properties,
- Super detergent / dispersant properties that assures cleaner engines,
- Exceptional resistance to oxidation thereby reducing the formation of deposits.

APPLICATIONS

Xtreme 7005 5W-30 is designed for use in typical service of gasoline and diesel engines operating under vehicle manufacturers' recommended maintenance procedures. This lubricant is suitable for extended drain intervals as specified by the engine manufacturers and for use in high performance gasoline and direct injection diesel engines.

**PERFORMANCE
LEVELS AND
APPROVALS**

API SL/CF
ACEA A1/B1-A5/B5
FORD WSS-M2C913A - WSS-M2C913B - WSS-M2C913C

**TYPICAL
CHARACTERISTICS**

| Xtreme 7005 5W-30 | TEST PROCEDURE | TYPICAL VALUES |
|----------------------------------|-----------------------|-----------------------|
| SAE Viscosity Grade | | 5W-30 |
| Density @15°C, Kg/m ³ | ASTM D 1298 | ≥850 |
| Kinematic viscosity @100°C, cSt | ASTM D 445 | 9,3÷12,5 |
| Viscosity Index | ASTM D 2270 | ≥155 |
| Pour Point, °C | ASTM D 97 | ≤-33 |
| Flash Point, °C | ASTM D 92 | ≥220 |