

**PRODUCT DESCRIPTION** | Xtreme OUTBOARD 4T 25W-40 is a high-performance lubricant developed for four-stroke outboard engines operating under severe conditions.

Xtreme OUTBOARD 4T 25W-40 features the following characteristics:

- Excellent protection against wear and salt corrosion,
- Outstanding oxidation resistance and remarkable thermal stability, allowing the lubricant's characteristics to be maintained in service,
- High detergent/dispersant power reducing deposit and sludge formation,
- Good compatibility with engine gaskets and valve stem seals,
- Excellent engine cleanliness and minimizes oil consumption.

**APPLICATIONS** | Xtreme OUTBOARD 4T 25W-40 is recommended for use in all modern high-performance four-stroke engines produced by MERCURY, BOMBARDIER, HONDA, MARINER, SELVA, SUZUKI, TOHATSU, VOLVO PENTA, YAMAHA, and where NMMA FC-W oils are recommended. It is recommended to adhere to the specifications and provisions of the manufacturers.

**PERFORMANCE LEVELS AND APPROVALS** | API SM  
NMMA FC-W/FC-W Catalyst compatible

**TYPICAL CHARACTERISTICS**

Xtreme OUTBOARD 4T 25W-40	TESTING PROCEDURES	TYPICAL VALUES
SAE grade	-	25W-40
Density @15°C, kg/m <sup>3</sup>	ASTM D 1298	≥ 865
Kinematic Viscosity @100°C, cSt	ASTM D 445	12,5 ÷ 16,3
Viscosity Index	ASTM D 2270	≥ 135
Pour Point,°C	ASTM D 97	≤ -27
Flash Point,°C	ASTM D 92	≥ 220
TBN, mg KOH/g	ASTM D 2896	7,0 ÷ 7,5