

**PRODUCT DESCRIPTION**

Xtreme 3007 10W-40 is a premium quality multigrade synthetic lubricant blended with isomerised base oil through a severe hydrogenation process and selected additives, designed to achieve the highest performance standards in gasoline and diesel engines.

Xtreme 3007 10W-40 offers the following main advantages:

- good low temperature properties to allow rapid lubrication after cold starting,
- outstanding protection against wear to maximise engine life,
- excellent detergent/dispersant properties for best soot control,
- excellent thermal and oxidation stability increasing fuel economy and extended service intervals.

**APPLICATIONS**

Xtreme 3007 10W-40 is intended for use in typical gasoline and diesel engine services, including turbo-charged engines in passenger cars, SUVs, light vans and light trucks. It is suitable for extended drain intervals as specified by engine manufacturers.

**PERFORMANCE LEVELS AND APPROVALS**

API SN  
MB 229.3  
VW 505.00/505.01

**TYPICAL CHARACTERISTICS**

<b>Xtreme 3007 10W-40</b>	TESTING PROCEDURE	RESULTS
SAE grade	-	10W-40
Density @15°C kg/ m <sup>3</sup>	ASTM D 1298	≥860
Kinematic viscosity @100°C,cSt	ASTM D 445	12,5 ÷ 16,3
Viscosity index	ASTM D 2270	≥130
Pour point, °C	ASTM D 97	≤-30
Flash point, °C	ASTM D 92	≥220