

PRODUCT DESCRIPTION

Xtreme 8001 C3 ECO SYNT 5W-30 is a last generation synthetic lubricant blended with carefully selected base oils and additives and formulated to guarantee outstanding performances in the modern naturally aspirated and turbocharged gasoline and diesel engines even in harsh work conditions. It is fully compatible with anti-pollution (eg. DPF-Diesel Particulate Filter) and exceeds the main OEM performance requirements.

APPLICATIONS

Xtreme 8001 C3 ECO SYNT 5W-30 is recommended in all new generation cars, sport utility vehicles and light truck engines.

PERFORMANCE LEVELS AND APPROVALS

ACEA C3
API SN PLUS
MB 229.51
BMW LL-04
VW 505.00/ 505.01
GM Dexos 2
PORSCHE C30

TYPICAL CHARACTERISTICS

8001 C3 ECO SYNT 5W-30	TESTING PROCEDURE	TYPICAL VALUES
SAE grade	-	5W-30
Density @15°C, kg/m ³	ASTM D 1298	≥849,6
Kinematic viscosity @100°C, cSt	ASTM D 445	9,3 ÷ 12,5
Viscosity index	ASTM D 2270	≥ 150
Pour point, °C	ASTM D 97	≤-33
Flash point, °C	ASTM D 92	≤210
TBN, mg KOH/g	ASTM D2896	≥7