

PRODUCT DESCRIPTION

Xtreme ATF D is formulated with selected base oils and appropriate additive package in order to give the product the properties required by Dexron IID specification.

This lubricant shows following properties:

- high Viscosity Index,
- good thermal and oxidation stability,
- good properties to low temperature,
- good compatibility with metals and elastomers used.

APPLICATIONS

Xtreme ATF D is recommended for automatic gearboxes, power steering systems, torque converters, hydraulic systems and all those automatic transmissions where a product ATF Dexron IID product is required.

The main advantages are:

- high anti-wear properties for surface protection in metal to metal contact,
- excellent anti-corrosion properties,
- special friction properties giving smooth and efficient operation of the transmissions,
- longer power steering and synchro life.

PERFORMANCE LEVELS AND APPROVALS

GM DEXRON IID
FORD MERCON/ M2C 138CJ
DTFR 13C100(MB 236.1)
MB 236.5
CAT TO-2
ALLISON C4
MAN 339D
ZF TE-ML-04D/09A/11A/14A/17C

TYPICAL CHARACTERISTICS

ATF D	Testing procedure	Typical Values
Color	Visual	Red
Density @15°C, kg/m ³	ASTM D 1298	≥850,0
Kinematic viscosity @40°C, cSt	ASTM D 445	≥37,0
Kinematic viscosity @100°C, cSt	ASTM D 445	≥7,0
Viscosity index	ASTM D 2270	≥150
Pour point, °C	ASTM D 97	≤-33
Flash point, °C	ASTM D 92	≥200